ECU OIL AUXILIARY



Materials	
External case	Polyamide
Insulating material	Polyurethane resin

Technical Data	
Power Supply	10 ÷ 16 Vdc
Maximum current	10 A
Stand-by current	200 µA
IP Grade	IP67
Operating temperature range	-20/+70 °C
Storage temperature range	-20/+80 °C
Weight	530 g
Connectors	1 x FCI Sicma 24 ways
Comunications	1 x CANBUS 2.0B
Inputs	6 x digital input NPN with internal pull up
Outputs	8 x solenoid valve max 1A
Technical Data	/

For any Technical Information, please contact our Sales Area

DATE	REV. N°	OBJECT	MOD. BY
DATE	REV. N°	OBJECT	MOD. BY
DATE	REV. N°	OBJECT	MOD. BY
DATE	REV. N°	OBJECT	MOD. BY

Drawing properties of MC Electronics. All rights reserved.

DESCRIPTION			PAGE
ECU OIL AUXILIARY			1/1
PART NUMBER	COD. DRAW	DRAWER	DATE
20CEN-0006	DS036_R0	BA	09/07/2020
MEASUREMENT UNIT	VIEW	TOLERANCE mm	SCALE
IS		+/- 0.2	1:3

MC ELECTRONICS
Fiesso Umbertiano - Rovigo - ITALY

Certified Quality System
UNI EN ISO 9001:2015
Certified Nr. 50 100 1361